

Fuji Spray Auto™ H-V8™ HVLP Spray Gun



6863G-H-V8	H-V8 Spray Gun - Spray Gun Only
6863G-H-V8-A	H-V8 Spray Gun with 600cc Aluminum Cup
6863G-H-V8-N	H-V8 Spray Gun with 600cc Nylon Cup

Best suited for base and clear coat applications, the **H-V8™** features a precise side-mounted fan pattern control and 360° swivel air inlet providing you with a convenient spray experience with every use. The **H-V8™** has few internal components, a forged aluminum gun body with anodized fluid passages, and an optimized HVLP air cap resulting in a soft spray pattern.

TIP SIZE	
Size (mm)	Part Number
1.2	6890H-V8-1.2
1.3	6890H-V8-1.3
1.4	6890H-V8-1.4
1.7	6890H-V8-1.7
2.0	6890H-V8-2.0
2.2	6890H-V8-2.2

SPECIFICATIONS	RECOMMENDED 14.7 CFM AT 28 PSI
Air Cap Sets Available (in mm):	1.2; 1.3; 1.4; 1.7; 2.0; 2.2
Operating Range:	9-28 psi
Air Inlet Size:	1/4" BSP and NPS
Air Supply Hose:	6.5 x 10 mm
Air Consumption:	14.7 cfm
Fluid Coupler:	3/8" PF
Standard Air Cap Set:	1.4 mm
Weight (without cup):	521 g (18.38 oz)
Application Type:	Waterborne and solvent-borne high-solid clear coat
Max. Fan Width:	325 mm
Paint Cup Adapters	S15 (3M™) DPC-31 (DeKups®) A14 (Colad)