

Fuji Spray Auto™ **LX-20™** HVLP Spray Gun



6260P-LX-N-14K	LX-20 Pressure Fed - Spray Gun Only + Extra 1.2 & 1.7mm
6265G-LX-C-14K	LX-20 Gravity with 600cc Nylon Cup + Extra 1.2 & 1.7mm
6265G-LX-N-14K	LX-20 Gravity - Spray Gun Only + Extra 1.2 & 1.7mm

Featuring a nearly 13” wide fan pattern and an enhanced HVLP air cap design, **The Fuji Spray® LX-20™** and its optimized air passages will decrease time in the spray booth and increase productivity. Easily adaptable to leading disposable cup systems, the **LX-20™** is intuitive, lightweight, and easy to maintain. The **LX-20™** features a unique comfort grip that reduces operator fatigue allowing you to spray for extended periods of time.

TIP SIZE	
Size (mm)	Part Number
1.0	6200LX-1.0
1.2	6200LX-1.2
1.4	6200LX-1.4
1.7	6200LX-1.7
2.0	6200LX-2.0

SPECIFICATIONS	RECOMMENDED 15.2 CFM AT 26 PSI
Air Cap Sets Available (in mm):	1.0; 1.2; 1.4; 1.7; 2.0
Air Supply Pressure:	26 psi (Gun Inlet) 1.8 bar
Air Inlet Size:	1/4” BSP and NPS
Air Supply Hose:	5/16” ID
Air Consumption:	15.2 cfm
Fluid Coupler:	M 16 x 1.5P
Standard Air Cap Set:	1.4 mm
Weight (without cup):	502 g (17.70 oz)
Application Type:	Waterborne and solvent-borne high-solid clear coat
Max. Fan Width:	330 mm
Paint Cup Adapters	S2 (3M™) DPC-11 (DeKups®) A09 (Colad)

*The LX-20 is also available as a pressure feed spray gun.